

Visible, the ultimate localization-light-system!



To be visible to your colleagues during operations in smoke-filled structures is of high importance to ensure that the operation is conducted in a safe way.

With Visible mounted on your SCBA air cylinder you will gain visual contact between you and your colleagues and in that way, you can easily keep track of and locate each other during the operations.

Visible will give you visual contact for a minimum of 5 meters / 16 feet in dense black smoke without a dazzling light and you will immediately see if your colleague falls or collapses and can then get to their aid directly for an extraction to safety and for treatment.



The system is available for:

SIEBE GORMAN
INTERSPIRO
DRÄGER
SCOTT
FENZY
MSA
ISI

Manufacturer: TexConLight AB, Sweden.

Battery: 2 AA batteries, lifetime fixed light 27 hrs. Twinkling light 100 hrs.

Heat: endures 300°C (570°F) for 4 hrs. and 800°C - 900°C (1470°F-1650°F) for 8-10 seconds.

Flame temperature: 850 C° (1560°F) fulfils IEC 335-1.

Water: The system is washable and stands rinsing with water when cleaning.

Warranty: 2 years on everything except the silicone cover and batteries.

Frame: Made of stainless steel.

Patent: Patent Pending.

Approvals: IMO (A.752 (18 §8) / CE / Light wire IP67

Visible: Can be seen for minimum 5 meters (16 feet) in dense black smoke without a dazzling light and over 200 meters (220 yards) in clear darkness.

Input V: 3V

Operating V: <110V

Intensity A: <0.05 A per 100 meter.

Isolation V: 4000V (IEC 335-1)

Storage temp °C: -40° to 80°

Optical wavelength nM: 505 nM at 400 Hz. Dynamic nF: 5.3 – 7.5 nF/m

Visible is made to stand up to all requirements for firefighting safety equipment worldwide.

We at TexConLight AB is proud to announce that preformed test made in Sweden and USA by professional firefighters shows that Visible stands up to what we state in our product specifications and beyond...

Visible will even work as a "safety tool" outside a smoke-filled structure as a warning light for drivers of approaching vehicles etc. Visible can be seen for at least 200 meters / 220 yards in clear darkness.

BE SAFE - BE VISIBLE

Notice!
Use alkaline 1.5 Voltage
AA size batteries only!

How to replace batteries



Fig.1 Unscrew the
lockscrew



Fig.2 Remove the clip



Fig.3 and 4. Lift up the whole unit and pull the hood
gently backwards to open the battery compartment



Fig. 4



Fig.5 Close
the cover of the battery
compartment



Fig.6 Remount the
Silicone hood



Fig.7 Remount the clip



Fig. 8

Fig.8 Tighten the screw too
ensure that the silicone
cover seals the inverter

Visit www.texconlight.se for instruction on video



info@texconlight.se

www.texconlight.se

Phone: +46 (0) 703 77 65 97